MT-50

TSUNAMI* PRODUCTS

APPLICATIONS & FEATURES:

- 6-12 Person Team Element
- Forward Operating Bases
- UTV Mountable
- Heavy-Duty Construction
- Corrosion-Resistant Aluminum
- 2 Person Carry

Mator Production

Dispensing



MT-50 SPECIFICATIONS

water Production	Potential: 15 US gallons/day at 80°F @ 80% RH
Internal Water Storage	4.5 US gallons
Energy Cost	\$0.16/gallon (assumes \$0.10/kW power cost)
Air Filtration	High efficiency, multi-layer poly fiber - washable & reusable
Water Filtration	Carbon filtration & LED ultra-violet light
Refrigerant	R-407C
Power Requirements	110 V ac, 50/60 Hz, 1phase
Power Draw	0.8 to 1.0 kW-hr, 10 amps (20 amp breaker)
Dimensions, W x L x H	20.25" x 30.25" x 26.75"
Weight	125 lbs
Mobility Feature	Heavy duty spring loaded handles to all allow two man carry

Hose bib valve for easy filling of any container





Pelican[©] Carry Case

Pelican AL3834-1617FT/HL

- Robust, RotoMolded Polyethylene Construction
- Steel Latches throughout, Heavy-Duty Injection-Molded Carry Handles
- Custom Polyurethane Foam Insert that Acoomodates MT50 Unit + Extra Water Filters, UV LED Lamp, Air Filters, and Power Inverter
- Size (LxWxD): 41"x37"x38"

WWW.TSUNAMIPRODUCTS.COM